



Art.No 29105 - 01

Calcium acetate

Description Calcium acetate is a powder which is used as a hardening agent for mineral oil based Blasocut emulsions, acting as an antifoam.

Properties Efficient, long-term antifoam for use in Blasocut emulsions. The water hardness, together with Blasocut, forms fine calcium soap which effectively prevents foaming.

Not to be used, since not effective, with Vasco 5000, synthetic Grindex and Synergy products.

When to use it When fresh or used Blasocut emulsions show an increased foaming tendency, especially in soft water or if the permissible water hardness is not reached.

How to use it Dosage: 30 g calcium acetate per 1'000 liters of emulsion hardens by 1° dH
17 g calcium acetate per 1'000 liters of emulsion hardens by 1° fH
17 g calcium acetate per 1000 liters of emulsion hardens by 10 ppm

Handling/Storage Protect against moisture.
Storage: Store in closed original container at temperature from +5°C to +40°C (41°F to 104°F).
Protect against frost. Do not expose to direct sunlight.

Transport: No hazardous good according to ADR

Safety and environmental aspects Check warning on packaging.
EC - waste code 06 03 14. Water endangering class 1
For more detailed information please consult the EC Safety Data Sheet.

Information contained in this data sheet is based upon the properties and applications of use as known to us. However, generally no legal liability may be deducted from such information.

S002 09.03.2015 V 07